

# OMS Model AV200 & AV300 Automated Turntable Stretch Wrapper

- Integrated Turntable Roller Conveyor
- 250-300% Power Pre-Stretch
- Operator Panel for Settings/Diagnostics
- Automatic film securing, cutting & sealing

## Features and Benefits

### Easy Integration into existing lines

Quick installation with minimal modification.

### Easy Film Reel Changeover

Operator friendly film loading maximises uptime.

### Automatic Film Application

Clamp holds film before it is automatically attached to the rotating pack.

### Film Overlap Control

Adjustable film reel vertical traverse speed controls amount of film overlap.

### Automatic film securing, cutting and sealing device

Film tail is cut by hot wire at end of cycle and applied to pack with hot pad (no loose film tails).

### Automatic Height Detector

Pack height recognition ensures machine is compatible with multiple sized pallets.

### 90 Degree Pack Rotation Option

Pack can continue along the line or rotate and be indexed off at 90 degrees after wrapping.

### Optional Equipment

Top Sheet Dispenser, Pneumatic Top Press (both standard on AV300), Increased Tower Height (max. pack dims 2700mm).

### Safety Guarding Options

Gordian can supply and install perimeter safety guarding if required.



Film Stretch	Polyethylene
Film Thickness	17-35micron
Film Width	500mm
Rotary Table Height	300mm
Rotary Table Diameter	1800mm
Production Speed	50-60 pallets/hr
Pallet Dims	800x1200 or 1000x1200mm
Max Pallet Weight	1500kg
Pallet Height (Standard Model)	With Press 1500mm Without Press 2100mm

Air Pressure	6bar
Air Consumption	13 NI/cycle approx.
Power Supply	400-415V, 3Ph – 50/60Hz
Power Consumption	2kW

***Dimensions and specifications will vary according to customer requirements.***