

OMS Model TR SERIES STRAPPING HEADS

- Easy strap loading, auto re-feed and strap in place signal as standard
- Consistent tension achieved on each and every strap
- Long Lasting, Self-Cleaning Heater Blades for PET Strap usage
- 200,000 cycles between services



Features and Benefits

Models to Suit All Industries

TR14, TR14HD (0-2300N), TR18, (0-4000N), TR19HT (0-7000N).

Proven & Reliable Technology

Electronic tension monitoring via load cell, calibrated circuit board and panel mounted potentiometer.

Fast, Consistent Strap Feed & Alignment

Precise, repeatable strap feeding alignment avoids jams and increases up-time.

Strap Compatibility

All heads are compatible with Polyester or Polypropylene Strap.

Rapid Head Replacement

Strapping Head is easily removed in 15 mins by releasing the retaining bolts and 3 electrical connectors.

Optional Auto Strap Feed

Enables feeding of strap into the head from a remotely sited coil holder (ideal where the head is in an elevated position).

Reduced Maintenance Costs

Modular, long lasting components such as cutters and heater blades are easily exchanged meaning less spares held in stock and increased uptime.

Strap/ Coil Options	Polyester or Polypropylene
Strap Width	9-19mm dependent on head
Strap Thickness	0.5- 1.3mm dependent on head
Strap Tension	0 to 700kg dependent on head
Tensioning Speed	0.25m/sec
Strap feed + recovery speed	2.5 or 5.5m/sec
Power Supply	230-400V, 50/60Hz
Noise Level	<70 db

Dimensions and specifications are subject to change without notice.